

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

| | |
|----------------------|--|
| SD. OR COPY RECEIVED | |
| DISTRIBUTION | |
| DATE | |
| FILE | |
| M.T.O.S. | |
| LAND OFFICE | |
| OPERATOR | |

OLEO CONSERVATION DIVISION

P.O. BOX 2200
ALBUQUERQUE, NEW MEXICO 87501

Form O-101
Revised 10-1-73

DO NOT USE THIS FORM FOR DRILLING PERMIT APPLICATIONS

RECEIVED

DEC 17 1981

O. C. P.

ARTESIA, NM 88210

Old Well New Well Other

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

G 1980

North

1980

UNIT LETTER

East

36

5S

24E

THE SECTION

15. NE 1/4 of 1/4 section (NW 1/4 of SW 1/4, etc.)

3864' GR

County

Chaves

Check Appropriate Box to Indicate Nature of Activity, Report or Other Data

NOTICE OF INTENTION TO:

SUSEQUENT REPORT OF:

PERFORM REHABILITATION WORK

PLUG AND ABANDON

REOPEN WORK

ALTERING CASING

TEMPORARILY ABANDON

CHANGE PLANS

CONTINUE DRILLING OPER.

PLUG AND ABANDONMENT

PULL OR ALTER CASING

CLOSING UP AND ABANDON

OTHER

Perforate & Treat

17. Describe proposed or completed operations (Clearly state all pertinent details, including approximate dates, including the earliest of starting any proposed work) SEE RULE 1103.

TD correction: TD 4250'. WIH and perforated 3668-3916' w/16 .40" holes as follows 3668, 70, 71, 74, 75, 76, 88, 3894, 96, 98, 3904, 06, 08, 12, 14 & 16'. Acidized perforations 3894-3916' w/2000 gallons 10% Spearhead acid and 9 ball sealers. Acidized perforations 3668-3677' w/1500 gallons 10% Spearhead acid. Sand frac perforations 3894-391' and 3668-3677' w/80000 gallons gelled KCL water and 20000 gallons CO₂ w/16000# 20/40 sand. Well stabilized and flowed 145 psi on 3/4" choke = 2206 mcf/d.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Engineering Secretary

SIGNED

DATE

12-16-81

APPROVED BY

W.A. Grossert

TITLE

SUPERVISOR, ENGINEERING

DATE

DEC 23 1981

CONDITIONS OF APPROVAL, IF ANY: