

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>YATES PET. CORP.</u>		Lease <u>ROOK "RK" ST.</u>		Well # <u>1</u>	
Location of Well	Unit <u>190N 660E H</u>	Section <u>16</u>	Township <u>8S</u>	Range <u>25E</u>	County <u>CHAVES</u>
Drilling Contractor	<u>LEM</u>		Type of Equipment <u>ROTARY</u> <u>12/4/81</u>		

★ WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	40.5# J-55		1030	950 SX. CIRC.
7 7/8" or 6 1/4"	4 1/2" or 5 1/2"	10.5# or 15.5#		4410	

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 14 3/4" Size of Casing 10 3/4" Sacks cement required 700 SXs.

Type of Shoe used TEXAS PATCHED Float collar used insert Btm 3 jts welded Yes

TD of hole 1030 Set 1030' Feet of 10 3/4 Inch 40.5 # Grade J-55

New-used csg. @ 1030 with 300 sacks neat cement around shoe 2% CaCl.

+ 400 sax HALLIBURTON LITE additives W/3% CaCl.

Plug down @ 7:00 (AM) (PM) PM Date 12-6-81

Cement circulated YES No. of Sacks 50 to the pit.

Cemented by HALLIBURTON Witnessed by Darry Brooks.

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: DRLNG. W/100% RETURNS. HARD AT TD.