

NEW OIL CONS. COMMISSION
UNITED STATES
DEPARTMENT OF THE INTERIOR
Artesia, NM 88210
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction, re-verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 38343

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Michael Eric

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T7S, R26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Sanders Petroleum Corporation

3. ADDRESS OF OPERATOR

11000-D Spain Road NE, Albuquerque, NM 87111

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FN & 1/4 WL, Sec. 22, T7S, R26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3739 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set 8-5/8" csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Received approval 10:00 p.m. 10-6-81 from Mr. Roger Chapman, USGS, to change depth of 8-5/8" casing to 700' after drilling 100' of anhydrite with salt stringers. Drilling water (fresh) had increased to 9.8#/gal.

Set 8-5/8" 24# J-55 API casing at 752' in anhydrite 10-7-81. Cemented (Western) 8-5/8" casing with 490 sx. Pacesetter "C" 3% CaCl₂, plus 150 sx. "C" 2% CaCl₂. Plug down 11:30 a.m. 10-7-81. Tested casing and BOP to 1500 psi before drilling out. (Circulated cement; circulated out 150 sx.)

RECEIVED
OCT 13 1981OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE 10-8-81

(This space for Federal or State office use)

(Orig. Sgd.) ROGER A. CHAPMAN

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side