JMOGD, GOPY

Form Approved.

- Budget Bureau No. 42-R142

ARTESIA, OFFICE

UNITED STATES					
DEPARTMENT OF THE INTERIOR					
GEOLOGICAL SURVEY					

5.	LEASE
NM	23264

SALT PEDERAL

9. WELL NO.

6.	IF INDIAN.	ALLOTTEE	OR	TRIBE	NAM:

				BECE	A. 455.79
				REL:	U 18. 4d
7	UNIT	AGREEMENT	NAME	• • • • • • • • • • • • • • • • • • • •	

SUNDRY NOTICES AND REPO	DRIS ON WELLS
And proposals to drill or to dee	pen or plug back to a different
Do not use this form for probability to proposals.)	

1.	cil Ezs X other
	NAME OF OPERATOR MESA PETROLEUM CO./
	ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4.	LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17
	AT SURFACE: 660' FSL & 1780' FWL

UNDESIGNATED_ABO

11. SEC., T., R., M., OR BLK, AND SURVEY OR AREA

SEC 4, T8S, R23E-

10. FIELD OR WILDCAT NAME

12. COUNTY OR PARISH 13. STATE CHAVES NEW MEXICO

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4022.9! GR

REQUEST FOR APPROVAL TO: SUBSE

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other) SPUD, 8 5/8" CSG & CEMENT

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

SUBSEQUENT REPORT OF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL A CITO U.S. GEOLOGICAL SURVEY LOSWELL, REVY MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 12 1/4" hole on 8-21-81. Drilled to 1500' and ran 38 jts 8 5/8", 24#, K-55 casing set at 1495'. Cemented with 800 sx HLW + 1# flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. Cement did not circulate. Ran five plugs with a total of 1025 sx Thixset + 4% CaCl + 1260 gal flocheck to circulate cement. Tested BOPs and casing to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled ahead on 8-25-81.

NOTE: Cement job witnessed by J. Wade/USGS

C: USGS (g,, TES, CEN RODS. A My Name March ard Type (44)	CCTG, MEC, 4	DIPTRERS.	ROSWELL FILE	_ Ft
	RECORDE &	REGULATORN		SEPTEMBER 1, 1981	
APPROVED BY _ CONTINUES OF	SEP 2 1981	TOUR	DATE		
	ROSWELL, NEW PACKE	· Sand April 1911 (1915)	ir, Reverse Sice		