

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
MESA PETROLEUM CO. /
3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud, 8 5/8" & cement

SUBSEQUENT REPORT OF:

**RECEIVED**  
SEP 14 1981  
OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE NM-36651
6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Cindy Federal
9. WELL NO. 1
10. FIELD OR WILDCAT NAME Undesignated Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 24, T8S, R22E
12. COUNTY OR PARISH Chaves
13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3950.8' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 12 1/4" hole on 9-2-81. Drilled to 1427' and ran 32 jts 8-5/8", 24#, k55 casing set at 1417'. Cemented with 800 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 1:00 p.m. 9-4-81. Cement did not circulate. Ran temp survey - TOC at 470'. Set two plugs with a total of 250 sx Thixset + 4% CaCl. Circulated 25 sx. Tested BOP's and casing to 600 psi for 30 min-OK. Reduced hole to 7-7/8" and drilled ahead on 9-5-81. WOC total of 20 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL FILE

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER K. CHAPMAN REGULATORY COORDINATOR DATE 9-10-81

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

SEP 17 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO