

UNITED STATES *Arts*  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
- 
2. NAME OF OPERATOR  
MESA PETROLEUM CO. ✓
- 
3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME
- 
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
NM 40029
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
ALKALI FED COM
9. WELL NO.  
2
10. FIELD OR WILDCAT NAME  
UNDESIGNATED ABO
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC 33, T5S, R25E
12. COUNTY OR PARISH  
CHAVES
13. STATE  
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3745.5' GR

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- |                          |                          |
|--------------------------|--------------------------|
| TEST WATER SHUT-OFF      | <input type="checkbox"/> |
| FRACTURE TREAT           | <input type="checkbox"/> |
| SHOOT OR ACIDIZE         | <input type="checkbox"/> |
| REPAIR WELL              | <input type="checkbox"/> |
| PULL OR ALTER CASING     | <input type="checkbox"/> |
| MULTIPLE COMPLETE        | <input type="checkbox"/> |
| CHANGE ZONES             | <input type="checkbox"/> |
| ABANDON*                 | <input type="checkbox"/> |
| (other) 8 5/8" CSG & CMT |                          |

- [illegible]

RECEIVED  
OCT 29 1981 (NOTE: Rep ch)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole to 1820' on 10-25-81 and ran 40 jts 8 5/8", 24#, K-55 casing set at 1819'. Cemented with 800 sx HLW + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed-in with 300 sx "C" + 2% CaCl. PD at 4:00 PM, 10-25-81. Circulated 400 sx. Reduced hole to 7 7/8" and drilled ahead on 10-26-81. WOC total of 18 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

**SIGNED**

TITLE REGULATORY COORDINATOR

OR DATE OCTOBER 28, 1981

OCT 30 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY  
ROSSELL, NEW MEXICO