1117	
	Form Approved.
	Budget Bureau No. 42-R142

Dec. 1973		
UNITED STATES	5. LEASE 9 40 1 2 9 7 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
DEPARTMENT OF THE INTERIOR		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME を表する 名 よらず	
C/SF GEOLOGICATION		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
the net was this form for proposals to drill or to deepen or plug back to a different	A PARECEIVED	
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas 🕎	Spring rederar Spring 1001	
well well other	9. WELL NO.	
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME O. C. D.	
MESA PETROLEUM CO. /	Undesignated Abo ARTESIA, OFFICE	
3. ADDRESS OF OPERATOR		
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec 5, T6S; R26E	
below.)	12. COUNTY OR PARISH 13. STATE	
AT SURFACE: 660' FSL & 660' FWL	Chaves New Mexico	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Some		
Salle	- 14. APINO Depart - P. Silda Bush - Fills	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REPORT, OR OTHER DATA	3710. ' GR	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3/10. dk	
TEST WATER SHUT-OFF		
FRACTURE TREAT		
SHOOT OR ACIDIZE		
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9-330.)	
PULL OR ALTER CASING		
OULDED TONICS	& GAS	
	CONTRACT OF THE TOTAL OF THE TO	
(other) TD, 4 1/2" csq & cement ROSWELL,	NEW MEXICO	
Clearly sta	te all pertinent details, and give pertinent dates,	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and including estimated date of starting any proposed work and romes pertinent to this work.)*		
measured and true vertical depths for all markers and zones pertine	ent to this work.)* 설파설을 및 의견되었	
Drilled 7 7/8" hole to TD of 4250' on 9-24-81. Ran 105 jts 4 $11\sqrt{2}$ " $10\sqrt{5}$ $10\sqrt{5}$ $10\sqrt{5}$		
k55 casing set at 4221'. Cemented with 600 sx HLW + 10# salt + 1/4# Flocele		
K55 casing set at 4221. Cemented with 500 t	7% Halad 4 + 2/30% &FR-2. PD	
and tailed in with 450 sx "C" + 5# KCL + 3/10% Halad 4 + 2/10% CFR-2. PD at 1:00 p.m. 9-25-81. Cement did not circulate. Released rig at 12 midnight		
9-25-81. WOCU estimated to arrive 10-19-81.		
9-25-61. Wold estimated to airive to is sit	부위속성원	
	三日 - 19 Y 3 g - 19 とよる前	
XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND,	, PARTNERS, ROSWELL, FILE	
Subsurface Safety Valve: Manu, and Type Set @ Ft.		
18. I hereby certify that the foregoing is true and correct	0_20_81	
SIGNED TREGULATORY COUR	RDINATORATE 9-29-81	
(This space for Federal or State office use)		
00T = 1004		
APPROVED BY	DATE	
CONDITIONS OF APPROVAL, IF ANY:		
U.S. GEOLOGICAL SURVEY		
ROSWELL, NEW MEXICO		