

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

SEP 4 1981

2. NAME OF OPERATOR
MESA PETROLEUM CO.✓

O. C. D.
~~ARTESIA, OFFICE~~

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL & 1980' FEI
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>
SPUD	

--	--	--	--	--	--	--	--

SEP 2 1981 (NOTE: Re ch

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSVELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17-1/2" hole on 8-26-81. Hit 20 BBL/H fresh water at 25'. Drilled to 856', and ran 22 jts 13 3/8", 48#, H40 casing set at 854'. Cemented with 750 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 11:30 p.m. 8-29-81. Circulated 100 sx. Reduced hole to 11" and drilled ahead on 8-30-81. WOC total of 19 1/2 hours.

NOTE: Cement job witnessed by Coke/USGS

YC: USGS (3), TLS, CEN RCHS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE
 Subsurface Safety Valve: Manul. and Type _____ Set @ _____

18. I hereby certify that the foregoing is true and correct

8:55

R. E. Nathan

REGULATORY COORDINATOR, STATE

SEPTEMBER 1, 1981

ROGER A. CHAPMAN

APPROVED BY
COMMISSIONERS

SEP 2 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

* See Instructions on Reverse Side