

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/S

SUNDRY NOTICES AND REPORTS ~~ON~~ **RENEWED** WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

SEP 16 1981

2. NAME OF OPERATOR  
MESA PETROLEUM CO. /

O. C. D.  
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FSL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other)

8-5/8" csg & cement

RECEIVED  
SEP 11 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE

NM-14291

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

LLOYDS FEDERAL COM

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

WILDCAT ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 11, T9S, R25E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3516.1' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole to 1735' on 8-31-81. Ran 43 jts 8-5/8", 24# K55 casing set at 1735'. Cemented with 800 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 8:00 p.m. 8-31-81. Circulated 200 sx. Reduced hole to 7-7/8", tested BOPs and casing to 600 psi for 30 min-OK, and drilled ahead on 9-1-81. WOC total of 18 hours.

XC: USGS (6), TLS, GEN RODS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE  
Subsurface Safety Valve: Manul. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. P. Mathews

REGULATORY COORDINATOR

9-4-81

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

(This space for Federal or State office use.)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

SEP 14 1981

TITLE

DATE

U.S. GEOLOGICAL SURVEY

See Instructions on Reverse Side