

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/S  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
MESA PETROLEUM CO. ✓

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL & 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) SPUD, 8 5/8" CSG & CEMENT	<input type="checkbox"/>	<input type="checkbox"/>

AUG 27 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 12 1/4" hole on 8-17-81. Hit brackish water at 213' - TSTM. Drilled to 1610' without returns and ran 41 jts 8 5/8", 24#, K-55 casing set at 1600'. Cemented with 800 HLW + 1# flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 3:00 AM on 8-19-81. Cement did not circulate. Ran temp survey - TOC at 770'. Set 17 plugs with a total of 3100 sx Thixset + 4% CaCl and 24 yards or redi-mix to circulate cement. Drilled ahead on 8-22-81.

XC: USGS (3), TSL, CEN RCDS, ACCTG, MEC, PARTNERS, ROSWELL, FILE

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] REGULATORY COORDINATOR DATE AUGUST 25, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

AUG 31 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO