

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
MESA PETROLEUM CO. ✓

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL & 1980' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) 8 5/8" csg & cement

5. LEASE  
NM-40030

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Lodewick Fed Com

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Undesignated Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 8, T5S, R25E

12. COUNTY OR PARISH 13. STATE  
Chaves New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3861' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole to 1807' and ran 44 jts 8 5/8", 24#, K-55 casing set at 1807'. Cemented with 700 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 2:00 p.m. 1-24-82. Circulated 450 sx. Tested BOPs and casing to 600 psi for 30 min.-ok. Reduced hole to 7 7/8" and drilled ahead on 1-23-82. WOC total of 18 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Markos REGULATORY COORDINATOR DATE 1-26-82

APPROVED FOR RECORD  
APPROVED BY ROGER A. CHAPMAN  
CONDITIONS OF APPROVAL, IF ANY:

FEB 1 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE

DATE

\*See Instructions on Reverse Side

