	NM OIL CONS. COMMISSION Drawer					
7		- ¹⁹	l			
(May 1963)	May 1963)			oved. reau No. 42–R1424.		
DEPARIMENT OF THE INTERIOR verse side)			5. LEASE DESIGNATIO			
0/34	GEOLOGICAL SURVEY		NM-14983			
	Tor proposals to drill or to deepen or plut rate of "APFLICATION FOR PERMIT" for such be		6. IF INDIAN, ALLOTT S	EP 2 2 1981		
1.			7. UNIT AGREEMENT	MALE C D		
WELL GAS WELL X		ARTESIA, OFFICE				
2. NAME OF OPERATOR	S. FARM OR LEASE N	AME				
Yates Petrol 3. ADDRESS OF OPERATOR	Monaghan "QY	federal				
207 South 4t	9. WELL NO.					
4. LOCATION OF WELL (Report		10				
At surface		10. FIELD AND POOL, OR WILDCAT				
660'	' FSL & 660' FWL, of Sec. 34-	-T5S-R24E	Und. Abo 11. sec., T., R., M., OI SUBVEY OR AE Unit M - Sec. 34-T5S-	EA		
14. PERMIT NO.	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	$\frac{34-135}{12. \text{ COUNTY OB PARIS}}$	-K24E SH 13. STATE		
	4039'	GR	Chaves	NM		
16.				1 111		
	Check Appropriate Box To Indicate No					
NOTI	CE OF INTENTION TO:	SUBSEC	QUENT REPORT OF:			
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	KEPAIRING	WELL		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING	CASING		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONM	ENT*		
REPAIR WELL	CHANGE PLANS	(Other) (NOTE : Report result	ts of multiple completion	n on Well		
	(Other) (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti- tor the work location.					
nene to this work.)						
Spotted a 14-3/4"	hole at 1:30 PM 9-1-81. Ran	n 22 joints of 10-3/	/4" 40.5# ST&C	casing		
	exas Pattern guide shoe set a					
w/650 sacks Class	"C" 3% CaCl. Compressive si	trength of cement 18	375 psi in 12 H	nours.		
PD 8:30 PM 9-3-81.	. Bumped plug to 500 psi, re	eleased pressure & f	float held okay	y •		
Circulated 50 sack	ks. WOC. Drilled out at 2:30	0 PM 9-4-81. WOC 18	hours. Nippl	led up &		
	I, OK. Reduced hole to 7-7/8					
	ugs for lost circulation as a liled in w/100 sx Thixolite, I					
	L. WOC 6 hrs. Tagged cemen					
	ked M_O pill. Got full retu					
2# Permacheck & 2%	CaCl ^g plug at 1056'. PD 1:	00 PM 9-8-81. WOC 1	18 hrs. Tagged	cement at		
1024'. Drilled pl	lug at 7:00 AM 9-9-81.					
	jts of 4-1/2" 9.5# K-55 ST&C	casing set at 4030'	. 1-Auto fill	l shoe set		
at 4030'. Cemente	= d w/350 ex 50/50 Poz 6% C	F-9 37 TF-/ & 37 F		DM 0 12 01		
Bumped plug to 120				PH 9-13-01.		

18. I here	by certify that the foregoing is true and correct		
SIGNE	D ACCEPTED FOR RECORD	TITLE Engineering Secretary	DATE <u>9-15-81</u>
(This	space tor Pederal of State Ance use)		
APPR	ITIONS OF SEPONALS 1984:	TITLE	DATE
	U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO	ee Instructions on Reverse Side	



n n a second a second