Form 9-331

Artesia, NM 88210

Form Approved.
- Budget Bureau No. 42-R1424

Dec. 1973	
UNITED STATES	5. LEASE 94 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
DEPARTMENT OF THE INTERIOR	NM 20932 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
C/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME 2 # 841
	OCT 1 3 198
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME 1 2 4 5
1. oil gas 🖂	STEWART FEDERAL 5 0 C D
well well other	9. WELL NO.
2. NAME OF OPERATOR	2
MESA PETROLEUM CO.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	UNDESIGNATED ABO
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA SEC 1, T8S, R24E
below.) AT SURFACE: 1980' FNL & 660' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	CHAVES E NEW MEXIGO
AT TOTAL DEPTH:	14. API NO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3745.6 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	4644 7 4 4
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE) Report results of multiple completion or zone
PILL OF ALTER CASING TO THE TOTAL OF THE TOT	Change on Form 9-330.)
MOLTIPLE COMPLETE	981 川澤 美麗
CHANGE ZONES	
(other) SPUD, 13 3/8" CSG & CEMENT U.S. GEOLOGICA	LISTIPACE 가는 기계 하는 그 관련성부 및 다
ROSWELL, NEW	MEXICO 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertinent to this work.)*	
•	
Spudded well with 17 1/2" hole on 9-26-81.	Drilled to 2011 and from 18 3ts
13 3/8", 48#, H-40 casing set at 756'. Cer	mented with ROP sylliw + 1 # Flocele
+ 4% CaC1, 300 sx Thixset + 4% CaC1, and ta	ailed in with 200 sx 'C' + 2% CaCl.
PD at 11:30 AM 9-29-81. Cement did not ci:	roulate. Tagged TOC at 155! Set
nine plugs with a total of 1710 sx Thixset	+ 4% CaCl to circulate cement.
Reduced hole and drilled ahead on 10-1-81.	WOC total of 42 hours.
Notabou IIII - III - III	
	그 그는 그는 아동사들은 종화 공원하다
XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC,	PARTNERS, ROSWELL, FILE
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby centify EPSEthe Con egging RD true and correct	
POGER ACTION DECLINATORY COORD	INATORATE October 4, 1981
SIGNED A. Z. FRANCE TIREGULATURI COURD	DATE
OCT 7 1981 (This space for Federal or State of	fice use)
	DATE
CONDITIONS OF APPROVAL IF ANY SURVEY	

ROSWELL, NEW MEXICO