

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
MESA PETROLEUM CO.✓

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

below.)
AT SURFACE: 1980' FNL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: SAME

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

5. LEASE

NM 20932

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
STEWART FEDERAL

9. WELL NO.

10. FIELD OR WILDCAT NAME
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 1, T8S, R24E

12. COUNTY OR PARISH	13. STATE
CHAVES	NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3745.6' GR

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) TD, 8 5/8" CSG, 4 1/2" CSG & CEMENT

SUBSEQUENT REPORT OF:

REPORT OF: **DECEIVE**
OCT 13 1981 (NOTE: Report change)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" to 1672' and ran 40 jts 8 5/8", 24#, K-55 casing set at 1669'. Cemented with 725 sx HLW + 1 flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. Circulated 50 sx WOC 18 hours, tested BOP's and casing to 600 psi - OK, reduced hole to 7 7/8" and drilled ahead on 10-3-81. Drilled to TD of 3850' on 10-4-81. Ran 94 jts 4 1/2", 10.5#, K-55 casing set at 3835'. Cemented with 600 sx HLW + 10# salt + 1/4# flocele and tailed in with 450 sx "C" + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD at 4:30 AM 10-5-81. Cement did not circulate. Released rig at 6:00 AM 10-5-81. WOCU estimated to arrive 10-16-81.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE Set @

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

18. Thereby, ACCEPTED FOR RECORD REGULATORY COORDINATOR OCTOBER 9, 1981
SIGNED ROGER A. CHAPMAN TITLE DATE

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO