He, or topics accepts	
OIL CONSERVATION DIV RECEIVED DISTRIBUTION P. O. BOX 2088	Form C-103 · Revised 10-1-
SANTA FE, NEW MEXICO 87501	Keyised 19-1-
OCT - 9 1981	Sa. Indicate Type of Lease
U.S.O.S.	State X Fee
O. C. D.	5, State Oil & Gas Lease No.
ARTESIA, OFFICE	L-6274
	MINITED TO THE TOTAL OF THE TOT
SUNDRY NOTICES AND REPORTS ON WELLS  [DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  [DO NOT USE TAPPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.]	
USE "APPLICATION FOR PERMIT (FORM C-TUT) FOR SUCH PROPUSACS.	7. Unit Agreement Name
OIL GAS X OTHER-	
Name of Operator	8. Farm or Lease Name
	Dee OQ State
Yates Petroleum Corporation /	9. Well No.
	2
207 South 4th St., Artesia, NM 88210	10, Field and Pool, or Wildcat
• = -	Und. Abo
UNIT LETTER P 660 FEET FROM THE SOUTH LINE AND 660 FEET FROM	
East 32 5S 25E	
East 32 5S 25E NMP	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3763' GR	Chaves
	191111111111111111111111111111111111111
Check Appropriate Box To Indicate Nature of Notice, Report of O NOTICE OF INTENTION TO:  PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING TEST AND CEMENT JOB X	F
OTHER	
OTHER	
(C) - he see - B review details and give nestinget dates including	a estimated date of starting any propos
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includit work) SEE RULE 1703.	
Spudded a $14-3/4$ " hole at $10:00$ AM $10-4-81$ . Ran 23 joints of $10-3/4$	
casing and Texas pattern guide shoe set at 926'. Flapper float at 8	: C 37 PaClo
w/200 sacks Pacesetter Class C 2% CaCl2. Tailed in w/500 sacks Class	
w/200 sacks Pacesetter Class C 2% CaCl2. Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-	81. Bumped
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ	81. Bumped ulated 50 sacks.
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to
w/200 sacks Pacesetter Class C 2% CaCl <sub>2</sub> . Tailed in w/500 sacks Class Compressive strenght of cement - 1875 in 12 hours. PD 4:30 PM 10-5-plug to 500 psi, released pressure and float held okay. Cement circ WOC. Drilled out at 4:30 AM 10-6-81. WOC 12 hours. Nippled up and	81. Bumped ulated 50 sacks. tested to

Thereby certify that the Information above is true and complete to the best of my knowledge and belief.

THE Engineering Secretary

OATE 10-8-81

THE SUPERVISOR, DISTRICT II DATE OCT 1 4 1981

ENDITIONS OF APPROVAL, IF ANYI