

Drawer DD  
Artesia, NM

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

- |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|

RECEIVED  
NOV 3 1981 (NOT RECORDED)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3770' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole to 1550' on 10-26-81. Ran 35 jts 8 5/8", 24#, K-55 casing set at 1550'. Cemented with 800 sx HLW + 1# flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 2:30 PM 10-27-81. Cement did not circulate. Ran temp survey - TOC at 820'. Required to set 3 plugs with 400 sx Thixset + 4% CaCl and gravel to fill annulus per J. Brasfield/USGS. Tested BOPs and casing to 600 psi for 30 mins - OK. Reduced hole to 7 7/8" and drilled ahead on 10-28-81. WOC total of 28 1/2 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

- 18. I hereby certify that the foregoing is true and correct**

SIGNED R. E. Martin TITLE REGULATORY COORDINATOR DATE OCTOBER 29, 1981

ACCEPTED FOR RECORD  
 APPROVED BY ROGER A. CHAPMAN  
 CONDITIONS OF APPROVAL, IF ANY:

NOV 16 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

**\*See Instructions on Reverse Side**