

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Stevens Operating Corporation /
3. ADDRESS OF OPERATOR
P. O. Box 2203, Roswell, New Mexico 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Sec. 11-7S-25E, 660' N, 660'W
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Production casing

SUBSEQUENT REPORT OF:

☐
☒
☒
☐
☐
☐
☐
☐
☐

RECEIVED
NOV 5 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM-43524
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Edmondson Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Undesignated Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 11-7S-25E
12. COUNTY OR PARISH
Chaves
13. STATE
N.M.
14. API NO.
30-005-61140
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3795 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 10-24-81 Ran 102 joints of 4 1/2" 10.5#, set in cement at 4100' w/250 sacks self stress and 3% CaCl₂. Pressure up 1000# for 30 min. logging no pressure decrease.
- 10-27-81 Perforate 3944.5, 45, 49.5, 50, 52.5, 53, 53.5, 57.5, 58, 58.5, 66, 66.5, 68, 68.5, 69, 72.5, 73.
- 10-28-81 Acidize w/3500 gals 7 1/2% HCL and 60,000 SCF N₂.
- 10-29-81 Frac w/41,500 gals 75% Quality Foam and 61,000# 20/40 sand and 625,000 SCF N₂.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE President DATE 11-4-81

(This space for Federal or State office use)

APPROVED NOV 17 1981
CONDITIONS OF APPROVAL:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side