

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
Artesia, NM 88210NM 88210 TRAP  
(Other Instructions  
Page 818)DATE  
ISSUEForm approved.  
Budget Bureau No. 42-R1424.

C/SF

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		DEC 14 1981	
2. NAME OF OPERATOR Sanders Petroleum Corporation ✓		O. C. D.	
3. ADDRESS OF OPERATOR 11000-D Spain Road NE, Albuquerque, NM 87111		ARTESIA, OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  1980' FSL & 1980' FWL		5. LEASE DESIGNATION AND SERIAL NO. NM 29610	
14. PERMIT NO.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4147 GL		7. UNIT AGREEMENT NAME	
		8. FARM OR LEASE NAME Huggins Draw	
		9. WELL NO. #1	
		10. FIELD AND POOL, OR WILDCAT Wildcat Und. 2nd	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, 5S, 24E 1980' FSL & 1980' FWL	
		12. COUNTY OR PARISH Chaves	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run casing and cement

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set 4-1/2" 10.5# K55 seamless API casing at 4212'. Dowell cemented with 240 sx. 65/35 Poz 4% gel with 8# Kolite plus 1/4# Celloflake per sack, plus 210 sx. "Self-Stress". Plug down 7:00 p.m. 10-27-81. Top of cement by temperature survey 2670'. Top of float collar 4173'.

RECEIVED  
NOV 20 1981OR A GAS  
U.S. GEOLOGICAL SURVEY  
ROSWell, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Assistant

DATE 11-18-81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side