

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

L CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

### SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator MESA PETROLEUM CO. ✓		8. Farm or Lease Name ACME COM
3. Address of Operator 1000 VAUGHN BUILDING/MIDLAND 79701-4493		9. Well No. 4
4. Location of Well UNIT LETTER N 660-990 SOUTH 1730-1980 THE WEST LINE, SECTION 30 TOWNSHIP 8S RANGE 26E NMPM.		10. Field and Pool, or indicate UNDESIGNATED ABO
15. Elevation (Show whether DF, RT, GR, etc.) 3676' GR		12. County CHAVES

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well with 17 1/2" hole on 10-10-81. Drilled to 838' and ran 21 jts 13 3/8", 48#, H-40 casing set at 837'. Cemented with 800 sx HLW + 1# flocele + 4% CaCl, 300 Sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 10:00 PM 10-11-81. Cement did not circulate. Ran temp survey - TOC AT 480'. Set five plugs with a total of 1050 sx Thixset + 4% CaCl to circulate cement. Reduced hole to 11" and drilled ahead on 10-13-81. WOC total of 20 hours.

XC: NMOCD (3), TLS, CEN RCDS, ACCTG, ROSWELL, MEC, PARTNERS, FILE, REM

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Mathews TITLE REGULATORY COORDINATOR DATE OCTOBER 15, 1981

PROVED BY W. L. Williams TITLE OIL AND GAS INSPECTION DATE OCT 20 1981

CONDITIONS OF APPROVAL, IF ANY: