

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Mesa Petr. Corp.</u>		Lease <u>Meadows Corn</u>		Well # <u>2</u>	
Location of Well	Unit <u>D</u>	Section <u>13</u>	Township <u>7</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor	<u>660/N</u> <u>660/W</u> <u>Desert Drilling</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>		<u>900'</u>	<u>300/200/300</u>
<u>11</u>	<u>8 5/8</u>	<u>24 #</u>		<u>1600'</u>	<u>500/300</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>10.5 #</u>		<u>4100'</u>	<u>500/500</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 17 1/2" Size of Casing 13 3/8" Sacks cement required \_\_\_\_\_

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

ID of hole 835' Set 835' Feet of 13 3/8" Inch 48 # Grade K-55

New used csg. @ 835' with 300 2%a sacks neat cement around shoe  
+ 700 sax Hall. Lite additives (1# flocc, 4% cc)

Plug down @ 3800 (AM) (PM) Date 12/29/81

Cement circulated No No. of Sacks -0-

Cemented by Halliburton Witnessed by Mike Stubblefield

Temp. Survey ran @ 9:00 (AM) (PM) Date 12/29/81 top cement @ 180'

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Wtr @ 275-300'

last day break @ 630'

No cementation