

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF  
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
MESA PETROLEUM CO. /

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
660' FNL & 660' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) 8 5/8" CSG & CMT

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE

NM 14756

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME  
GERRY FEDERAL DEC 14 1981

9. WELL NO. O. C. D. 1

10. FIELD OR WILDCAT NAME  
ARTESIA, OFFICE  
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 1, T8S, R25E

12. COUNTY OR PARISH 13. STATE

CHAVES NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3603.2' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole to 1845'. Ran 48 jts 8 5/8", 24#, K-55 casing set at 1845'. Cemented with 750 sx HLW + 1# flcele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD @ 4 AM. 12-3-81. Circulated 150 sx to surface. Tested BOPs and casing to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled ahead on 12-3-81. WOC total of 18 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE  
Subsurface Safety Valve: Manu. and Type Set @ . . . . . Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN  
REGULATORY COORDINATOR

DATE DECEMBER 7, 1981

(This space for Federal or State office use)

APPROVED DEC 11 1981  
CONDITIONS OF APPROVAL ANY:

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE

DATE