

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
MESA PETROLEUM CO.
3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Spud, 13 3/8" csg & cement



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 12-31-81. Started making 50 BW at 189' and increasing to 75 BPH at 460'. Sand caving in hole at 492'-set 300 sx Thixset to condition hole. Drilled ahead making 75-100 BPH at 460'-set second plug w/500 sx Thixset and drilled out on 1-4-82. Drilled to 910' and ran 23 jts 13 3/8", 48#, H40 casing set at 909'. Cemented with 750 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 8:00 p.m. 1-6-82. Cement did not circulate. Ran temp survey-TOC at 375'. Set three plugs with a total of 600 sx Thixset + 4% CaCl to circulate cement. Blew hole dry and waited one hour-no fluid. Reduced hole to 12 1/4" and drilled ahead on 1-8-82. WOC total of 36 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. F. Math TITLE REGULATORY COORDINATOR DATE 1-11-82

ACCEPTED FOR RECORD

ROGER A. CHAPMAN

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

JAN 20 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side