

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
MESA PETROLEUM CO.
3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) 8 5/8" csg & cement

5. LEASE
NM-40029
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME RECEIVED
8. FARM OR LEASE NAME
Alkali Fed Com JAN 25 1982
9. WELL NO.
5 O. C. D.
10. FIELD OR WILDCAT NAME
Undesignated ABO ARTESIA, OFFICE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 15, T5S, R25E
12. COUNTY OR PARISH 13. STATE
Chaves New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3772.4' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12 1/4" hole to 1820' and ran 43 jts 8 5/8", 24#, K-55 casing set at 1820'. Cemented with 750 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 2:30 p.m. 1-9-82. Circulated 200 sx to surface. Tested BOPs and casing to 600 psi for 30 min. - ok. Reduced hole to 7 7/8" and drilled ahead on 1-10-82. WOC total of 18 1/2 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM, PARTNERS, ROSWELL, FILE
Subsurface Safety Valve: Manu. and Type

Set @

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. Chapman TITLE REGULATORY COORDINATOR DATE 1-12-82

ACCEPTED FOR RECORD

ROGER A. CHAPMAN (This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

JAN 22 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side