

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1650' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐


MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) TD, 4 1/2" csg & cement

SUBSEQUENT REPORT OF:



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole to TD of 4150' on 1-11-82. Ran 100 jts 4 1/2", 10.5#, K-55 casing set at 4083'. Cemented with 500 sx "C" + 5# KCL + 3/10% HALAD-4 + 2/10% CFR-2. PD at 8:00 p.m. 1-12-82. Cement did not circulate. Released rig at 6:00 a.m. 1-13-82. WOCU estimated to arrive 1-25-82.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM, PARTNERS, ROSWELL, FILE

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. STARMAN

TITLE REGULATORY COORDINATOR

DATE 1-14-82

(This space for Federal or State office use)

APPROVED BY

JAN 22 1982

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO