

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

NM DISTRICT COMMISSION  
(Other instructions on re-  
drawer 50D)  
Artesia, NM 88210

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM 16069

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yellow Lake Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat Wind. Also

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 10, T8S, R24E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS BY

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

NOV 09 1984

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

O. C. D.

ARTESIA, OFFICE

3. ADDRESS OF OPERATOR

9720-B Candelaria, N.E., Albuquerque, N.M., 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

660' FNL, 1,980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,588' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

November 19, 1981:

1. Set 100' cement plug from 3,154' to 3,054' with 40 sacks Class "C" cement.
2. Set 100' cement plug from 1,056' to 956' with 60 sacks Class "C" cement.
3. Set surface plug with 10 sacks Class "C" cement.
4. Installed dry-hole marker and started rigging down.

RECEIVED  
NOV 23 1981

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

cc: WIO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Claudia Lesse*

TITLE Secretary

DATE 11/20/81

(This space for Federal or State office use)

PETER W. CHESTER

APPROVED

APPROVED BY  
CONDITIONS OF APPROVAL

NOV 8 1984

(Oris. S.S.) PETER W. CHESTER

DATE

NOV 8 1984

\*See Instructions on Reverse Side