

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
HUSKY OIL COMPANY

3. ADDRESS OF OPERATOR
600 S. Cherry St., Denver, CO 80209

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2050' FNL & 2100' FEL, SW/4 NE/4
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Ran Intermediate Casing

SUBSEQUENT REPORT OF:

RECEIVED
NOV 23 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 39 jts, 8-5/8", 24#, J-55, ST&C csg. FS @ 1569' KB.

Cemented - 150 sx Thixolight + 2% CaCl₂ + 2 pps Permacheck + 1/2 pps Celloseal.

Followed by - 415 sx Pacesetter light + 2% CaCl₂ + 1 pps Permacheck + 1/4 pps Celloseal.

Followed by - 500 sx Class "C" + 2% CaCl₂. 250 psi during cmtg. No returns. WOC.

---- Brantley Dickey, U.S.G.S., on location 11/15/81.

Ran temperature survey. TOC @ 910'.

RIH w/1" pipe - Spot 50 sx Thixolight cmt plug @ 910'. POOH w/1". Btm 19 jts plugged.

RIH w/1" pipe - Attempted to circ 130 BW; no returns. Spot 50 sx Thixolight cmt plug @ 825'. POOH w/1". Btm 6 jts plugged w/cmt.

RIH w/1" pipe - Tag cmt @ 740'. Spot 250 sx Class "C" + 2% CaCl₂. POOH w/1".

---- James Brasfield, U.S.G.S., on location 11/16/81.

RIH w/1" pipe - Tagged cmt @ 350'. Circ 30 BW. Spot 30 sx Class "C" + 2% CaCl₂. Circulated cmt to surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE Engr. Assistant DATE November 17, 1981

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

DEC 11 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.