		· · · ·			يستعير				
STATE OF NEW MEXIC	0					.IVED	30-	005-0	51167
ERGY AND MINERALS DEPAT		OIL	CONSERVAT	ION DIVIS	SION		orm C-101 levised 10-	1 70	
we, or correspectives			р. о. вох	2088	IAN 2	1 1982			
DISTRIBUTION		SAL	P.O. BOX NTA FE, NEW N	1EXICO 875	Run e		SA. Indicute		
SANTA FE		•			O. C.	<u> </u>	BTATE X		rcc [_]
r n. c.			0 0	1 1		. D .	5. State Off		No.
U.S.G.S.		Hm	ended	Locat	ARTESIA,	OFFICE	L-	6274	
DERATOR		•		•		E E	IIIII:	$\Pi\Pi\Pi$	111111
	N FOR PE	RMIT TO	DRILL, DEEPEN	, OR FLUG S	ACK .		//////	HHHH	HHHH
Type of Work							7. Unit Agre	ement Name	and also had and he had
Type of Well DRILL X			DEEPEN		PLUG B	ACK [_]]-	8. Form or L	easo Namo	
	•			SINGLE	MULT		Dee "O	Q" State	e
all CAS WELL WELL Y	<u>нто</u>	(R					9. Well No.	<u></u>	
Yates Petroleum Co	rnoratio	~ /					3		
iddress of Operator	rporatio						10. Field on	d Pool, or W	fildcat
207 S. 4th, Artesi		lovico	88210				/ Undesi	gnated .	АЪо
					North		11111Í	エルアブ	TITTT,
UNIT LETTE	• <u>A</u>	Loc	ATED 660	FLET FROM THE	NULLI		HHHH.	//////	HHHH
	T = = •		C OF NEC. 32	TWP. 5S	net 25	F NUPM	MM	HHHH.	HHHH
660 FITT FROM	THE East	mm	ITTTTTTTT	(IIIIII)	111111	بطوال سودهم مريدير متود اجب	12. County	11/	MMM ??
HHHHHHHH	HHHH	UUUU	HHHHH	ille an	HHH:	MIM	Chaves		HHHH
							777777	ولللكار	1. the the
HHHHHHHH	HHHH	HHH.	HHHHHH	HHHH		///////	IIIII	illili	ANNIE
			HHHHH	15. Frequeed by	- <u></u>	GAN NAMAA 3A. Furmation	アノファアナ	[59, listay - ママインアフラ	<u>x x x x x x x x x</u> cr C.T.
CHANNIN (CHANN)	HHHH	HHH	HHHHH	1		Abo		Rotar	.,
	777777	<u>//////</u> /	6 Status Plug. Frend	approx.		ALO	22. Applox	. Date Work	Character of the second s
Trevetions (Show whether D1;	<i>ici, eici</i>)				+ L+	mi	ASAF		
3762.5		Blan	ĸet	<u>eoric</u>	F				
		P	ROPOSED CASING A	ND CEMENT PRO	DGRAM	-			
SIZE OF HOLE	SIZE OF	CASING	WEIGHT, PER FOO	T SETTING	DEPTH	SACKS OF	CEMENT	EST	. тор
15"	10 3/4		40.5# J-5			800 sx		circu	lated
$\frac{15}{7.7/8"}$ or 6 1/4'			10.5#or 1			350 sx			
1 110 01 0 114	<u>`</u> 4								
	1		1	1		1		ł	

We propose to drill and test the Abo and intermediate formations. Approximately 975' of surface casing will be set and cement circulated to shut off gravel and caving. If needed (lost circulation) 7 7/8" intermediate casing will be run to 1650' and cemented with enough cement calculated to tie back into the surface casing. Temperature survey will be run to determine cement top. If commercial, production casing will be run and cemented with adequate cover, perforate, and stimulate as needed for production. <u>MUD PROGRAM</u>: FW gel and LCM 1650', brine to 3500', Brine & KCL water to TD, MW 10-10.2. We we we will be BOP PROGRAM: BOP's will be installed at approximately 1650' and tested daily. <u>APPROVAL VALID FOR / SO DAYS</u>

GAS NOT DEDICATED.

Williams TITLE OIL AND BAS INSPECTOR

ATE JAN 2 5 1982

PERMIT EXPIRES 7-22-82

UNLESS DRILLING UNDERWAY

V MEXICO OIL CONSERVATION COMMIS N WELL LOCATION AND ACREAGE DEDICATION PLAT

÷

-

Form C-102 Supersedes C-128 Effective 1-1-65

	All dist	ances must be from t	the outer boundaries of	the Section.	
perator		Lec			Well No.
	ROLEUM CORPORATI	DN I	Dee OQ Sta Bange		3
	tion Township 32	5 South	25 East	County Chaves	
A tual Footage Location		y 500 th	20 2030	Citaves	
	et from the North	line and	660 feet	from the East	line
ound Level Elev:	Producing Formation	Poo	1		Dedicated Acreage:
3762.5'	ARO		UNNES A	60	160 Acre
					he plat below. hereof (both as to workin
 If more than o dated by comm Yes 	ne lease of different o nunitization, unitization No If answer is '	n, force-pooling. "yes;" type of co	etc? nsolidation		f all owners been consol
this form if ne No allowable v	cessary.) vill be assigned to the	well until all int	erests have been c	onsolidated (by con	ated. (Use reverse side of munitization, unitization approved by the Commis
	1				CERTIFICATION
				660' tained he	certify that the information con train is true and complete to th by knowledge and belief.
		4PC. L-627	 4	Position Reg Company 4/ATE Date	<u>CowAn</u> <u>Coordinator</u> <u>spet Corp</u> 1-20-82
			- L JO	shown or notes of under my is true	certify that the well location this plat was plotted from field actual surveys made by me of supervision, and that the sam and correct to the best of m e and belief.
	 		Carlon Carlos	Date Survey Registered and/or Lan	1/18/82 Professional Engineer



15 FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

All preventers to be hydraulically operated with secondary manual controls installed prior to drilling out from under casing.

Choke outlet to be a minimum of 4" diameter.

- Kill line to be of all steel construction of 2" minimum diameter.
- . All connections from operating manifolds to preventers to be all steel. hole or tube a minimum of one inch in diameter.
- The available closing pressure shall be at least 15% in excess of that required with sufficient volume to operate the B.O.P.'s.
- . All connections to and from preventer to have a pressure rating equivalent
- to that of the B.O.P.'s.
- Inside blowout preventer to be available on rig floor.
- Operating controls located a safe distance from the rig floor.
- . Hole must be kept filled on trips below intermediate casing. Operator not responsible for blowouts resulting from not keeping hole full.
- D. P. float must be installed and used below zone of first gas intrusion.

51.0