

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ NOV 30 1981

2. Name of Operator
MESA PETROLEUM CO

3. Address of Operator
1000 VUAGHN BUILDING/MIDLAND, TEXAS 79701-4493

4. Location of Well
UNIT LETTER G 1780 NORTH 1980
EAST 30 8S 26E
THE LINE, SECTION TOWNSHIP RANGE NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
ACME

9. Well No.
7

10. Field and Pool, or Wildcat
UNDESIGNATED ABO

12. County
CHAVES

15. Elevation (Show whether DF, RT, GR, etc.)
3668' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well with 17-1/2" hole on 11-14-81. Drilled to 848', making 100 bbl/hour fresh water. Ran 21 jts 13-3/8", 48#, H40 casing set at 840'. Cemented with 700 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 10:30 a.m. 11-16-81. Cement did not circulate. Tagged cement with 1" at 420'. Set two plugs with a total of 450 sx Thixset + 4% CaCl to circulate cement. Reduced hole to 11" and drilled ahead on 11-17-81. WOC total of 20-1/2 hours (including 8 hours WOC after last plug).

NMOCD(3), TLS, CEN RCDS, ACCTG, ROSWELL, MEC, PARTNERS, FILE, REM

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R E North TITLE REGULATORY COORDINATOR DATE 11-20-81

APPROVED BY M R Williams TITLE OIL AND GAS INSPECTOR DATE DEC 1 1981

CONDITIONS OF APPROVAL, IF ANY: