Form 9-331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERION C/SF GEOLOGICAL SURVEY Dravier Dravier D	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.) 1. oil well gas well 2. NAME OF OPERATOR	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Godfrey MP Federal 9. WELL NO. 6 ARTESIA, OFFICE
Yates Petroleum Corporation / 3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FSL & 660' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	10. FIELD OR WILDCAT NAME H Nituration K Nituration K 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit I, Sec 10-T7S-R25E 12. COUNTY OR PARISH 13. STATE Chaves NM 14. APL NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF X FRACTURE TREAT X SHOOT OR ACIDIZE X PULL OR ALTER CASING X MULTIPLE COMPLETE X CHANGE ZONES X	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3800' GR (NOTE: Report results of multiple completion or zone 1981 (thange on Form 9-330.)
(other)	te all pertinent details, and give pertinent dates.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 40' of 20" conductor pipe. Spudded a 14-3/4" hole at 12:00 noon 11-4-81. Ran 21 joints of 8-5/8" 10-3/4" 40# H-40 casing set at 851'. 1 guide shoe at 851'. Cemented w/200 sacks Howco Lite and 2% CaCl₂. Tailed in w/200 sacks Class C 3% CaCl₂. PD 12:30 AM 11-6-81. Bumped plug to 800 psi, released pressure and float held okay. Cemented circulated 35 sacks to pit. WOC. Drilled out 12:30 PM 11-6-81. WOC 12 hours. Nippled up and tested to 1000 psi, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

Subsurface Safety Valve: N				Set @
18. I hereby certify that y SIGNED LE AROGER A	PON BESINGRE true an	nd correct		
SIGNED LE AROGER A	CHAPMAN	TITLE Engineering	Secty Date	11-11-81
NOV	1 ô 1981 (The	s space for Federal or State	office use)	
ADDOVED BY	SANAL SURVEY	TITLE	DATE	· · · · · · · · · · · · · · · · · · ·
ROSWELL	NEW MEADER	ç		

*See Instructions on Reverse Side

×.

ŝ.

-FÌ