

NM OIL CONS. COMMISSION

Drawer DD

Artesia, NM 88210

Form Approved.
Budget Bureau No. 42-R1424

sf/file

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)
AT SURFACE: 1980' FSL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.
REPORT, OR OTHER DATA:

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Production Casing, Perforate

SUBSEQUENT REPORT ON:

☒

☒

☐

☐

☐

☐

☐

RECEIVED
DEC 09 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4260'. Ran 102 joints of 4-1/2" 9.5# K-55 ST&C casing set at 4225'. 1-notched guil shoe at 4225'. Insert flipper float at 4189'. Cemented w/450 sacks 50/50 Poz, 2% gel, 2# KCl, .3% Halad 4 and .2% CFR-2. PD 7:15 PM 11-29-81. Bumped plug to 750 psi released pressure and float held okay. WOC. WIH and perforated 3684-3985' w/13 .50' holes as follows: 3684-89', 3715-19, 3985-86'. Spotted 300 gallons MOD 101 acid over perforations. Sand frac perforations 3684-3986' w/1700 gallons MOD 101 acid, 40000 gallons gelled KCl water, 2 loads CO₂, 80000# 20/40 sand. Well cleaned up and flowed 140 psi on 3/4" choke = 2217 mcf/d.

Subsequent Safety Valves Marked in this Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

ACCEPTED FOR RECORD
SIGNED: ROGER A. CHAPMAN

Engineering Secty DATE 12-7-81

APPROVED BY
CONDITIONS OF APPROVAL: B. 200

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO