

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

APR 26 1982

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Bishop RY Com
9. Well No. 1
10. Field and Pool, or Wildcat Pecos Slope Abo
12. County Chaves

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - II" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓
Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 11 TOWNSHIP 6S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3854' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

REPAIR REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
WELL OR ALTER CASING ☐ OTHER ☐

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☐ OTHER Production Csg., Perforate, Treat ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4350'. Ran 108 joints of 4-1/2" 9.5# J-55 casing set at 4350'. 1-regular guide shoe at 4350'. Float collar at 4310'. Cemented w/375 sacks 50/50 Poz, .3% CFR-2, and 2# KCL. Compressive strength of cement - 1050 psi in 12 hours. PD 2:30 AM 4-7-82. Bumped plug to 1300 psi, released pressure and float held okay. WOC. WIH and perforated 3992-4007' w/11 .50" holes as follows: 3992, 93, 94, 95, 96, 97, 4004, 05, 06, 07, 08'. Acidized perforations w/2000 gallons 7 1/2% Morroflo acid. Sand frac'd perforations (via casing) w/120000# 20/40 sand. Well stabilized at 45 psi on 3/4" choke = 845 mcfpd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

PREPARED BY [Signature] TITLE Engineering Secretary DATE 4-22-82

APPROVED BY [Signature] TITLE SUPERVISOR, DISTRICT II DATE APR 28 1982

CONDITIONS OF APPROVAL, IF ANY: