

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 12-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG 7982

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
1. Name of Operator		
Sanders Petroleum Corporation		
2. Address of Operator		
11000-D Spain Road NE, Albuquerque, NM 87111		
3. Location of Well		
UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM		
THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>7S</u> RANGE <u>26E</u> NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name
McKay-Samedan
9. Well No.
#2
10. Field and Pool, or Wildcat
Undesignated Abo
12. County
Chaves

15. Elevation (Show whether DF, RT, CR, etc.)
3632 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Run casing and cement</u> <input checked="" type="checkbox"/>

## 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 12:30 p.m. 11-15-81. Set 8-5/8" 24# J55 casing at 840'. Cemented with 400 sx. 2% CaCl "C" followed by 200 sx. 2% CaCl "C". Circulated out 300 sx. Plug down 5:30 p.m. 11-17-81. Tested casing and BOP to 1500 psi before drilling out; WOC 18 hours before drilling out.

## 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Helen A. Hughes</u>	TITLE <u>Administrative Assistant</u>	DATE <u>11-18-81</u>
APPROVED BY <u>Mark Williams</u>	TITLE <u></u>	DATE <u>NOV 20 1981</u>
CONDITIONS OF APPROVAL, IF ANY:		