

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

C/SF  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Estoril Producing Corp.

3. ADDRESS OF OPERATOR 79701

11th Floor, Vaughn Bldg. Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FWL & 660' FNL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: "

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Casing & Cement

SUBSEQUENT REPORT OF:

☐

☐

☐

☐


☐

☐

☐

☐

☒



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/26/81 T.D. 4000'

Ran 102 joints, 4 1/2" 10.5#, J-55 ST&C casing (3998') set at 3998'. Cemented with 700 sacks Class 'C', 1# perma check/sk, 1# Cello Seal/sk, 2% KCL followed by 200 sacks, 50-50 Pozmix, .6% CF-9, .3% TF-4, 3% KCL. Full circulation throughout job.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. [Signature]

TITLE Agent

DATE 12/9/81

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE \_\_\_\_\_ DATE \_\_\_\_\_