UNITED STATES Artes1a, NM 88216. LEASE DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different servicit. Use form 9-331-2 for such proposals. 1. oil gas mell other 2. NAME OF OPERATOR Estoril Producing Corporation/ 3. ADDRESS OF OPERATOR 11 th Floor Vaughn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1930 'FNL & 660 'F.WL AT TOTAL DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA KEQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF KRACTURE TREAT HOT OR ACIDIZE KEPAIR WELL WINT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME 9. WELL NO. 7. UNIT AGREEMENT NAME 9. WELL NO. 7. C. D. 7. C. D.	Torm 9-331 Drawer DD	
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY MM-37845 SUNDRY NOTICES AND REPORTS ON WELLS Denote usits form for proposals. to drill or to dreate or plug back to a different well □ make bits form for proposals. To drill or to dreate or plug back to a different method. The form for proposals. To drill or to dreate or plug back to a different method. The form for proposals. To drill or to dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The form for proposals. The dreate or plug back to a different method. The dreate dreate or plug back to a different method. The dreate dreate or plug back to a different method. The dreate dreate or plug back to a different method. The dreate dreate dreate dreate dreate dreate dreate or plug back to a different method. The dreate dreate dreate dreate dreate dreate dreate method. The dreate dre	Dec. 1973	
GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7 Do not with the form for proposals to fifth or deepen or plug back to a different development back form a state of acch proposals. To deepen or plug back to a different development back form a state of acch proposals. The deepen or plug back to a different development back for acch proposals. The development of the develo		
C/251 Construction Million SUBDRY NOTICES AND REPORTS ON WELLS been on the this form for proposale deferrent of plug back to a different been on the this form for proposale deferrent of plug back to a different been on the form for proposale deferrent of plug back to a different been on the form for proposale deferrent of plug back to a different been on the form for proposale deferrent of plug back to a different below. 9. UNIT AGREEMENT NAME REC Enclose Shoehan Federal NOV 1 / 188 Shoehan Federal Nov 1		
SUNDRY NOTICES AND REPORTS ON WELLS 2. UNIT AGREEMENT NAME RECENCE SUNDRY INDICES AND REPORTS ON WELLS 2. UNIT AGREEMENT NAME RECENCE Do not we his form for proposals to define to the deepen or plug back to a different 8. FARM OR LEASE NAME 8. FARM OR LEASE NAME 1. oil well well well deter 0. C. D. 0. C. D. 2. NAME of OPERATOR 11 th THOOT Valghm Bldg. Midland Tx 1. designated Abo 3. ADDRESS OF OPERATOR 11 th THOOT Valghm Bldg. Midland Tx 1. designated Abo 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) ISEC. T. R. M. OR BLK AND SURVEY OR AT TOTAL DEPTH: Sade AT TOTAL DEPTH: Sade AT TOTAL DEPTH: Sade AT TOTAL DEPTH: Sade AGE AFROPRIST ON OT HELL (REPORT LOCATION CLEARLY. See space 17 below) 13. SEC. T. R. M. OR BLK AND SURVEY OR ART TOTAL DEPTH: Sade AT TOTAL DEPTH: Sade Set WATER SHUTOF SUBSEQUENT REPORT OF: IST WATER SHUTOF IST CLE REPORDS ON COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measure and true vertical detafts for all markers and zones pertinent details, and give pertinen	CUSE GEOLOGICAL SURVEY	
 Be not use this form for proposals to define to deepen or plug back to a different deference. Use form of proposals of the proposal of the proposals of the proposal of the proposal of the proposals of the proposals of the proposal of the proposals of the proposal o		
<pre>starver, Use Form 9-331-2 for such proposals) 1. oil gas well S other 2. NAME OF OPERATOR Estoril Producing Corporation/ 3. ADDRESS OF OPERATOR 11th Floor Vaughn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) At SURFACE: 19,80 'FML & 660'FML AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE; 7. REPORT, OR OTHER DATA KEQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4.102'GL NOTE: Report results of multiple completion or zone WULTPLE COMPLETE ULL OR ALTER CASING UNTIFIE ADDRESS UNTIFIE ADDRESS UNTIFIE ADDRESS DATE OF CASE & Coment A 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if well is directionally diffed, give subsurface locations and measured and true vertical depts for all markers and zones pertinent details, and give pertinent dates, including estimated date of starting any proposed work, if well is directionally diffed, give subsurface locations and measured and true vertical depts for all markers and zones pertinent to this work.'' Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (8/8'), 10 3/4" 32.75# ST&C casing and set at 674'. Cemented with 430 sacks of Class 'C' cement with 1% gel and \$# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% Cacl. Full circulation throughout job. Circulated 75 sacks of cement with 1% cacl. Full circulation throughout job. Circulated 75 sacks of cement with 1% cacl. Full circulation throughout job. Circulated 75 sacks of cement with the foregoing is true and correct </pre>	SUNDRY NOTICES AND REPORTS ON WELLS	V. ONTE AGREEMENT MARIE RECEIVED
1. oil well well well other Shechan Federal NOV 17 [39] 2. NAME OF OPERATOR Shechan Federal NOV 17 [39] 3. ADDRESS OF OPERATOR 3. O.C.D. 11th Floor Vaughn Bldg. Midland Tx 1. Sc.T.R.M. OR BUKANDS UNVEY OR APERATOR LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1930 'FNL & 660 'FNL AT TOP PROD. INTERVAL: Stephen Proposition of WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1930 'FNL & 660 'FNL AT TOP PROD. INTERVAL: Stephen Proposition of Subsequent REPORT OF: Sector of Proper PROPRIATE BOX TO INDICATE NATURE OF NOTICE, Stephen Proposition of Subsequent REPORT OF: IF REPORT, OR OTHER DATA Subsequent REPORT OF: Sector of Case & Comment A Subsequent REPORT OF: IF REPORT CASING Subsequent REPORT OF: IF DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is diffectionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (876'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 1% Cacl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. %.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type	Do not use this form for proposals to drill or to deepen or plug back to a different eservoir, Use Form 9–331–C for such proposals.)	
 Well Green Book Strategy Strat		
 2. NAME OF OPERATOR Estoril Producing Corporation/ 3. DORES of OPERATOR 11th Floor Vaughn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) At SURFACE: 1930 FENL & 660 F.NL AT TOP PROD. INTERVAL: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA 7. DUBSEQUENT REPORT OF: EENATER SHUT-OFF 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: RACIDER TREAT 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE: REPORT, OR OTHER DATA 7. DESCRIBE FROPOSED OR COMPLETE DOPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of storing any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (378'), 10 3/4" 32.75# ST&C casing and set at 874 '. Cemented with 430 sacks of Class 'C' cement with 1% cacl. Full circulation throughout job. Circulated 75 sacks of class 'C' cement to surface. P.O.B. 5:50 pm 11-8-81. *.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu and Type		,00
Estoril Producing Corporation/ 3. ADDRESS OF OPERATOR 11th Floor Valuephn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1930'FNL & 660'FNL AT JOP ARD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP ARD. INTERVAL: BED. ADD. YOUR CONTON EST WATER SHUT-OFF BED. MOLTE: WILL OR ALTER CASING JUL OF ALTER CASING JUL OF ALTER CASING JUL OF ALTER CASING JUL OR ALTER CASING		
 a. ADDERSS OF OPERATOR 11 th FLOOT Vaughn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) at SUFFACE: 1930'FNL & 660'FNL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: SAME CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA CHECK APPROVAL TO: SUBSEQUENT REPORT OF: CHECK APPROVAL TO: SUBSEQUENT REPORT OF: CHECK APPROVAL TO: SUBSEQUENT REPORT OF: CHOTE: Report results of multiple completion or zone (NOTE: Report results of multi		
11th Floor Vaughn Bldg. Midland Tx 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1930 'FNL & 660 'FNL AT TOP PROD. INTERNAL: AT SURFACE: 1930 'FNL & 660 'FNL AT TOP PROD. INTERNAL: BEC. T. R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T-53, R-24E 12. COUNTY OR PARISH 13. STATE Check APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA HEQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF HOOT OR ACIDIZE ULL OR ALTER CASING Subscrifted ENCOPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and tru		Indesignated Abo
 A. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SUBFACE: 1930'FNL & 660'FNL AT TOP PROD. INTERVAL: AT TOP ADDEPTH: Same G. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF WILL OR ALTER CASING WULL OR ALTER CASING WULL OR ALTER CASING WULL OR ALTER CASING WILL OR ALTER CASING <li< td=""><td></td><td></td></li<>		
A. DOWNION OF WELL (REPORT DOWNION CLEARCH: See space 17) Sec. 33, T-5S, R-24E AT SURFACE: 1930'TENL & 660'FML TOTAL DEPTH: Same AT TOTAL DEPTH: Same 12. COUNTY OR PARISH 13. STATE Check APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 14. API NO. REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) FQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EVENTURE TREAT Image on Form 9-330.3 MUITPLE COMPLETE Image		
AT SURFACE: 1980'FNL & 660'FNL AT TOTAL DEPTH: Same 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EXTURE REAT HOOT OR ACIDIZE ULL OR ALTER CASING ULL OR ALTER CASING ULL OR ALTER CASING DULL OR ALTER CASING HAMAGE ZONES HAMAGE ZONES HAMAGE ZONES HAMAGE ZONES HAMAGE ZONES HEANDON* other) SUFFACE CSE & Coment × Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 4# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% Co.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same G. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF HANGE CONDUCT ET WATER SHUT-OFF HANGE ZONES IBANDON' OTHER CASING ULL OR ALTER CASING INTERVENTION OF A COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 4# Cello-Seal per sack, followed by 300 sacks of Class 'C' cemert with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. %.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type MANG		
AT TOTAL DEPTH: SARE 4. API NO. 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 10.2' GL 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 17. DESCRIBE PROPOSED OR COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (378'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and ½# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. %.0.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type Set @	AT TOP PROD. INTERVAL:	
 Scheck APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: EST WATER SHUT-OFF IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (SHOW DF, KDB, AND WD) (10.2 ° GL IS. ELEVATIONS (STATE STATE STATE	AT TOTAL DEPTH: Same	
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ALIO2'GL ALIO2'CL	5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	· ·
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 4102' GL EST WATER SHUT-OFF	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
<pre>EST WATER SHUT-OFF</pre>		
 RACTURE TREAT HOT OR ACIDIZE HOT ACIDIZE HOT OR ACIDIZE HOT ACIDIZ	EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	· · · · · · · · · · · · · · · · · · ·
HOOT OR ACIDIZE		¹ State and Sta State and State
<pre>REPAIR WELL</pre>		
 PULL OR ALTER CASING		NOTE: Report results of multiple completion or zone
<pre>MULTPLE COMPLETE</pre>	PULL OR ALTER CASING \square	
 NBANDON*	AULTIPLE COMPLETE	
Surface Csg & Cement X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 890'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 1# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. #.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type Set @Ft.		
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 1# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 4% gel and 1# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement to surface. P.O.B. 5:50 pm 11-8-81. W.O.C. 12 hours. Pressure tested casing 1000-psi for 30 minutes. Subsurface Safety Valve: Manu. and Type Set @ Ft. 		
<pre>including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 14 3/4" hole 11-6-81. 11-8-81 390'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and ‡# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. #.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes.</pre>		
11-8-81 390'. Ran 23 joints (878'), 10 3/4" 32.75# ST&C casing and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 4# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. W.O.C. 12 hours. Pressure tested casing 1000.psi for 30 minutes. Subsurface Safety Valve: Manu. and Type Set @ Ft.	including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and
and set at 874'. Cemented with 430 sacks of Class 'C' cement with 4% gel and 1# Cello-Seal per sack, followed by 300 sacks of Class 'C' cement with 1% CaCl. Full circulation throughout job. Circulated 75 sacks of cement to surface. P.O.B. 5:50 pm 11-8-81. W.O.C. 12 hours. Pressure tested casing 1000 psi for 30 minutes. Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. Thereby centify that the foregoing is true and correct	NYWW IT JA HOLO II OUI	
18. I hereby centify that the foregoing is true and correct	and set at 874'. Cemented w cement with 4% gel and 4# Ce by 300 sacks of Class 'C' ce circulation throughout job. cement to surface. P.O.B. 5 12 hours. Pressure tested of	hith 430 sacks of Class 'C' llo-Seal per sack, followed ment with 1% CaCl. Full Circulated 75 sacks of 5:50 pm ll-8-81. W.O.C.
18. I hereby centify that the foregoing is true and correct		
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	18. I hereby c_{eff} that the foregoing is true and correct	
		11_9_81

「日本の

(Thi	s space for Federal or Sta	te office use)	
APPROVED BY ACCEPTED FOR RECORD	TITLE	DATE	
NOV 1 6 1981	See Instructions on Rev		
		erse side	
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO			

