

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

**RECEIVED**  
 NEW MEXICO OIL CONSERVATION COMMISSION  
**JUN 23 1983**  
**O. C. D.**  
**ARTESIA, OFFICE**

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG-0157

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator PETROLEUM DEVELOPMENT CORPORATION	7. Unit Agreement Name
3. Address of Operator 9720-B Candelaria N.E., Albuquerque, New Mexico 87112	8. Farm or Lease Name Marley Amoco State
4. Location of Well UNIT LETTER <u>L</u> <u>1,980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>7 South</u> RANGE <u>26 East</u> NMPM.	9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 3,911.63' GL	10. Field and Pool, or Wildcat Wildcat Abo
12. County Chaves	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/7/83 Pumped 20 sx. of class "C" cement w/4% CaCl<sub>2</sub> at 4,730'. P.U.H. W.O.C. 1 1/2 hrs. did not tag plug. Pumped 30 sx ditto. W.O.C. 1 hr. did not tag plug. Pumped 15 sx ditto pressured up to 2500 psi. P.U.H. W.O.C. 1 hr. Tagged cement plug at 4,460'. Circulated hole with gelled brine water with 25#/bbl. P.O.H. Perforated 4 1/2" casing @ 1,025'. Pumped 50 sx class "C" cement. Cement plug 820' in 4 1/2" casing and 820' in 8 5/8" casing. Shut in so cement wouldn't "U" tube.

6/8/83 Cemented with 5 sx class "C" cement at surface. Installed dry hole marker. Filled in pits, levelled and ripped location. Location is ready for inspection.

Part ID-2  
7-1-83  
P&A

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Gary L. Roberts TITLE Operations Manager DATE 6/21/83

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 CONDITIONS OF APPROVAL, IF ANY: