

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Spud, 13 3/8" csg & cement

5. LEASE  
NM-16324

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME DEC 15 1981

8. FARM OR LEASE NAME  
Charlotte Federal ARTESIA OFFICE

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Undesignated ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 30, T7S, R26E

12. COUNTY OR PARISH  
Chaves

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3625' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well with 17 1/2" hole on 11-16-81. Hit 50 BBL/hour fresh water at 520'. Drilled to 867' and ran 21 jts 13 3/8", 48#, H40 casing set at 866'. Cemented with 700 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 7:00 a.m. 11-18-81. Cement did not circulate. Ran temp survey - TOC at 55'. Blew hole dry - waited one hour - no fluid entry. Reduced hole to 12 1/4" and drilled ahead on 11-19-81.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Chapman  
ACCEPTED FOR RECORD

TITLE REGULATORY COORDINATOR

DATE 11-23-81

ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY DEC 14 1981  
CONDITIONS OF APPROVAL

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side