

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

NOV 2 1981

O. C. D.
ARTESIA, OFFICE

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

Type of Work

DRILL ☒DEEPEN ☐PLUG BACK ☐

Type of Well

OIL WELL ☐GAS WELL ☒OTHER ☐SINGLE ZONE ☐MULTIPLE ZONE ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street, Artesia, NM 88210

Location of Well

UNIT LETTER 0

LOCATED 660

FEET FROM THE South LINE

1980

FEET FROM THE

East

LINE OF SEC. 36

TWP. 7s

R. 24e

N. 10s

5A. Indicate Type of Lease

STATE ☒FCC ☐

5. State Oil & Gas Lease No.

LG-4352

7. Unit Agreement Name

8. Form or Lease Name

Snakeweed "SD" State

9. Well No.

1

10. Field and Pool, or Wildcat

Undes. Abo

12. County

Chaves

19. Proposed Depth

Approx. 4500'

19A. Formation

Abo

20. Rotary or C.T.

Rotary

21A. Kind & Status Plug. Bond

3818 GL

Blanket

21B. Drilling Contractor

L & M #2

22. Approx. Date Work will start

ASAP

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
15"	10 3/4"	40.5# J-55	1050	950	circulated
7/8" or 6 1/4"	4 1/2" or 5 1/2"	10.5# or 15.5#	TD		

We propose to drill and test the Abo and intermediate formations. About 1030' of surface casing will be set and cement circulated. If needed, 7 5/8" intermediate casing will be run to around 1500' with enough calculated cement to tie back in to the surface casing. Then run temperature survey to find top of cement. If commercial, production casing will be run and cemented with adequate cover, perforated and stimulate as needed for production.

MUD PROGRAM: FW gel and LCM to 1500'; Brine to 3200'; Drispak and starch to TD.

BOP PROGRAM: BOP's will be installed on 10 3/4" casing and tested daily.

GAS NOT DEDICATED:

APPROVAL VALID FOR 180 DAYS
PERMIT EXPIRES 5-5-82
UNLESS DRILLING UNDERWAY

BELOW SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTION ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

By Glen B. Baker Title Regulatory Manager Date Oct. 30, 1981

(This space for State Use)

APPROVED BY Mr. Williams TITLE OIL AND GAS SUPERVISOR DATE NOV 5 1981

REVISIONS OF APPROVAL, IF ANY:

Notify N.M.O.C.C. in sufficient
time to witness cementing

the 10 3/4" casing

NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102
Supersedes C-128
Effective 1-1-65

All distances must be from the outer boundaries of the Section.


Operator Yates Petroleum Corporation		Lease Snakewood "SD" State		Well No. 1
Unit Letter 0	Section 36	Township 7s	Range 24e	County Chaves
Actual Footage Location of Well: 660 feet from the South line and 1980 feet from the East line				
Ground Level Elev. 3818'	Producing Formation Alamo	Pool 1000'	Dedicated Acreage: Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☒ No If answer is "yes," type of consolidation _____

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name

Gliserio Rodriguez

Position

Regulatory Manager

Company

Yates Petroleum Corp.

Date

10-30-81

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed

October 29, 1981


Registered Professional Engineer
and/or Land Surveyor

[Signature]

Certificate No.

3690

EXHIBIT C



THE FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

1. All preventers to be hydraulically operated with secondary manual controls installed prior to drilling out from under casing.
2. Choke outlet to be a minimum of 4" diameter.
3. Kill line to be of all steel construction of 2" minimum diameter.
4. All connections from operating manifolds to preventers to be all steel, hole or tube a minimum of one inch in diameter.
5. The available closing pressure shall be at least 15% in excess of that required with sufficient volume to operate the B.O.P.'s.
6. All connections to and from preventer to have a pressure rating equivalent to that of the B.O.P.'s.
7. Inside blowout preventer to be available on rig floor.
8. Operating controls located a safe distance from the rig floor.
9. Hole must be kept filled on trips below intermediate casing. Operator not responsible for blowouts resulting from not keeping hole full.
10. D. P. float must be installed and used below zone of first gas intrusion.