

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESTIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Ref Corp</u>		Lease <u>Snake Woods</u>		Well # <u>1</u>	
Location of Well	Unit <u>P</u>	Section <u>36</u>	Township <u>7</u>	Range <u>24</u>	County <u>Chaves</u>
Drilling Contractor	<u>L-M #1</u>		Type of Equipment		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	<u>8 5/8</u>	<u>24</u>	<u>900</u>	<u>900</u>	

Casing Data:

Surface 21 joints of 8 5/8 inch 24 # Grade J-55

Yes (Approved) (Rejected)

Inspected by B.W.W. date 3-25-82

Cementing Program

Size of hole 14 3/4 Size of Casing 8 5/8 Sacks cement required

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 901 Set 825 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 140 with 250 sacks neat cement around shoe
+ .500 sack Pace Setter C additives 200 SX Thickmate

Plug down @ 1.00 (AM) (PM) Date 3-28-82

Cement circulated No No. of Sacks

Cemented by Western Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Ran Temperature Survey 10:00 Am 3-28-82 Top Cement @ 275