

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

30-005-61207

Form C-101
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	
OPERATION	1

RECEIVED

NOV 05 1981

5A. Indicate Type of Lease
STATE ☐ REC ☒
5. State Oil & Gas Lease No.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work
1b. Type of Well
DRILL ☒ DEEPEN ☐ PLUG BACK ☐
OIL WELL ☐ GAS WELL ☒ OTHER ☐
SINGLE ZONE ☒ MULTIPLE ZONE ☐

7. Unit Agreement Name

8. Farm or Lease Name

Adams

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat Abo

2. Name of Operator
ESTORIL PRODUCING CORPORATION ✓

3. Address of Operator
11th Floor Vaughn Bldg. Midland Texas 79701

4. Location of Well
UNIT LETTER C LOCATED 660 FEET FROM THE North LINE

AND 1980 FEET FROM THE West LINE OF SEC. 23 TWP. 4-S RGE. 23-E NMPM

12. County

Chaves

11. Elevations (Show whether DF, KT, etc.) 4321.0 GR	21A. Kind & Status Plug. Bond Blanket	19. Proposed Depth 4000	19A. Formation Abo	20. Rotary or C.T. Rotary
	21B. Drilling Contractor Tex Mex	22. Approx. Date Work will start Nov. 26, 1981		

23. PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2	13 3/8	48#	450	595	Surface
12 1/4	8 5/8	24#	1600	881	Surface
7 7/8	4 1/2	10.5#	4000	930	Surface

Blowout Prevention:

Schaeffer Model Double Ram BOP with 3400 psi working pressure with 4 1/2" pipe rams.

Posted ID-1
API + NL Books
11-13-81

APPROVAL VALID FOR 180 DAYS
PERMIT EXPIRES 5-9-82
UNLESS DRILLING UNDERWAY

IF ABOVE SPACE DESCRIBE PROPOSED PROGRAM; IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Harry W. Franklin Title Agent Date 11-4-81

(This space for State Use)

APPROVED BY W. Williams TITLE Oil and Gas Supervisor DATE 11-4-81

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to surface behind 13 3/8" casing