

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well
2. NAME OF OPERATOR
THE SUPERIOR OIL COMPANY
3. ADDRESS OF OPERATOR
P.O. Box 4500, The Woodlands, Tx 77380
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FWL of
AT TOP PROD. INTERVAL: Sec. 18
AT TOTAL DEPTH: straight hole
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Drilling Operations ☒

RECEIVED
JAN -4 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
MOSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-3-81 (5050'MD) POH with overshot after losing stabilizer & bit in hole. 9.3# MW.
12-4-81 (5050'MD) Washed to top of fish @ -5043'. POH. 9.1#MW.
12-5-81 (5050'MD) Recovered fish. 9.2# MW.
12-6-81 (5122'MD) Washed & Reamed 120' to bottom. Drilling 9.3# MW.
12-7-81 (5314'MD) Drilling ahead. Worked on drawworks brakes for 13-1/2 hrs. 9.4# MW.
thru
12-8-81
12-9-81 (5323'MD) GIH w/bit #10. Drilling. 9.7# MW.
12-10-81 (5773'MD) Drilling ahead. 9.4# MW.
thru
12-12-81

CONTINUED ON BACK

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. Bannantine TITLE Reg. Group Mgr. DATE 12-29-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

USGS (6), RG

ACCEPTED FOR RECORD
ROGER A. CHAPMAN

*See Instructions on Reverse Side

JAN 12 1981

U.S. GEOLOGICAL SURVEY

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

12-13-81	(5783'MD)	Drilling.	Prep. to log.	9.4# MW.
12-14-81	(5783'MD)	Logged well.	9.5# MW.	
12-15-81	(5783'MD)	Waiting on orders.		
12-16-81	RIH to 5565'	open ended DP.	Circ. & conditioned hole.	
	Cemented first plug @ 5565'-5415'	w/60 sks Class H.	LD 66 jts DP.	
	Cemented 2nd plug @ 3575'-3425'	w/80 sks. Class H.	LD DP.	
12-17-81	Set 80 sks. plug 1655'-1485'.	POH w/5 std. DP.	WOC.	
	LD DP.	Released rig @ 1400 hrs.	12-17-81.	