

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF  
**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
MESA PETROLEUM CO.✓
3. ADDRESS OF OPERATOR  
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL & 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: SAME
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒

(other) 8 5/8" CSG & cement - lost hole

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM 27970
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
COYOTE FEDERAL
9. WELL NO.  
7
10. FIELD OR WILDCAT NAME  
UNDESIGNATED ABO
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC 5, T7S, R25E
12. COUNTY OR PARISH  
CHAVES
13. STATE  
NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3869' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole to 1703' and ran 45 jts 8 5/8", 24#, K-55 casing set at 1703'. Cemented with 750 sx HFW + 1#/sx Flocele + 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD @ 2:30 PM 11-24-81. Cement did not circulate. Ran temp survey - TOC @ 340'. Went in hole to 740' - hit metal. Casing appears to have parted. Attempts to squeeze and drill out failed. Cement was circulated by 1 inching with 270 sx Thixset + 4% CaCl. Moved rotary rig off hole at 6:00 AM 12-3-81. WOCU to P&A well. Estimated to arrive 12-5-81.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. P. [Signature]

TITLE REGULATORY COORDINATOR DATE DECEMBER 3, 1981

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

DEC 11 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE

