

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
MESA PETROLEUM CO.

3. ADDRESS OF OPERATOR
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Spud, 13 3/8" csg. & cement

5. LEASE

NM-40030

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
LODEWICK FEDERAL

DEC 15 1981

9. WELL NO.
3

10. FIELD OR WILDCAT NAME
UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC 17, T5S, R25E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3843.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 11-18-81. Drilled to 802' and ran 20 jts 13 3/8", 48#, H40 casing set at 801'. Cemented with 800 sx HLW + 1# Flocele + 4% CaCl, 300 sx Thixet + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 10:00 a.m. 11-22-81. Cement did not circulate. Ran temp survey - TOC at 400'. Set three plugs with a total of 600 sx Thixet + 4% CaCl to circulate cement. Blew hole dry and waited one hour-no fluid entry. Reduced hole to 12 1/4" and drilled ahead on 11-23-81. WOC total of 28 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, LAND, PARTNERS, ROSWELL, FILE

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

TITLE REGULATORY COORDINATOR

DATE 11-24-81

(This space for Federal or State office use)

APPROVED BY DEC 14 1981
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO