

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Cibola Energy Corporation

3. ADDRESS OF OPERATOR
P.O. Box 1668, Albuquerque, New Mexico 87103

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FWL & 1980' FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Total Depth 8183', PBTD 8140'

We propose to plug this well as follows:

1st plug, 15 sacks Class C Cement with 3% CaCl, 8140-8000' to cover perfs.

~~2nd plug, 15 sacks Class C Cement with 3% CaCl, 7680-7500' to cover top of~~

~~Siluro Devonian~~ P.W.C. 9/14/82

3rd plug, 35 sacks Class C Cement with 3% CaCl, 7400-6900' to cover perfs at 7348-54' and top of Mississippian.

4th plug, 15 sacks Class C Cement with 3% CaCl, 5970-5800' to cover top of Wolfcamp.

5th plug, 20 sacks Class C Cement with 3% CaCl, 5300-5050' to cover top of Abo.

WOC overnight then run freepoint on 4 1/2" casing, then cut and pull all free 4 1/2".

6th plug, 35 sacks Class C Cement centered over 4 1/2" stub.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Operations Manager DATE September 1, 1982

APPROVED

(This space for Federal or State office use)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

SEP 24 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

5. LE. PY
NM 14472

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Agua Negra

8. FARM OR LEASE NAME

Agua Negra

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8-9S-28E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3904.4 Gr.

SEP 3 1982

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

- 7th plug, 35 sacks Class C Cement with 3% CaCl, 2625-2500' centered over 8 5/8" shoe, this plug will be tagged.
8th plug, 35 sacks Class C Cement with 3% CaCl, 1780-1680' to cover top of San Andres formation.
9th plug, 35 sacks Class C Cement with 3% CaCl, 1220-1120' to cover top of Queen
10th plug, 35 sacks Class C Cement with 3% CaCl, 570-⁴⁷⁰~~670~~' to cover 13 5/8" stub.
11th plug, 15 sacks Class C Cement at surface with dry hole marker.

↑ This plug to be eliminated if BLM wants to use as water well

Location will be cleared of junk and levelled and will be ready for inspection by October 30, 1982.