

RECEIVED BY

AUG 01 1985

O.C.D.

SUNDARTS OFFICE

NM OIL CONS. COMMISS

Drawer DD

S Artesia, NM 88210

DEPT OF THE INTERIOR

GEOLOGICAL SURVEY

NM 14472

6. IF INDIAN, ALLOTTEE OR INDIAN NAME

7. UNIT AGREEMENT NAME

Agua Negra

8. FARM OR LEASE NAME

Agua Negra

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8-9S-28E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3904.4 Gr.1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Cibola Energy Corporation

3. ADDRESS OF OPERATOR

P.O. Box 1668, Albuquerque, New Mex.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990 FWL &amp; 1980 FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐

(other)

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☒

OIL &amp; GAS

MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged well as follows:

10-12-82 1st plug, 15 sacks Class C Cement with 3% CaCl, 8140-8000'  
 2nd plug, 15 sacks Class C Cement with 3% CaCl, 7680-7500'  
 3rd plug, 35 sacks Class C Cement with 3% CaCl, 7400-6900'  
 4th plug, 15 sacks Class C Cement with 3% CaCl, 5970-5800'  
 5th plug, 20 sacks Class C Cement with 3% CaCl, 5300-5000',  
 tagged.

10-13-82 Cut 4 1/2" casing to 4760' and pulled 92 joints, slips  
 let loose and dropped back in hole.

10-14-82 Tagged fish at 3584', but could not get into it.

OVER

Subsurface Safety Valve: Manu. and Type

Set @

Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Sec.

DATE November 15, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

APPROVED  
PETER W. CHESTER

JUL 30 1985

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side

# Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional offices, and practices, are or are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item A: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant potential for production; any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional offices, and practices, are or are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

GPO : 1976 O - 214-148

10-16-82 Tagged fish at 3584' and pumped 50 sacks Class C Cement with 3% CaCl. Pulled 6 stands and WOC 2 hours. Tagged plug at 3394' and pulled up to spot next plug, pumped 35 sacks Class C Cement at 2635'.  
 10-18-82 Pumped final 3 plugs after tagging plug at 2496'.  
 35 sacks Class C Cement with 3% CaCl 1792-1663'  
 35 sacks Class C Cement with 3% CaCl 1216-1087'  
 35 sacks Class C Cement with 3% CaCl 576-448', tagged.  
 Released rig and shut in well for BIM.  
*Shut in water well*  
*pu*