

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Clement Energy, Inc.</u>		Lease <u>King 35 Corn</u>		Well # <u>1</u>	
Location of Well	Unit <u>Q</u>	Section <u>35</u>	Township <u>14</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>1980-S</u> <u>1980-E</u> <u>Cactus Drilling</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48 #</u>		<u>375'</u>	<u>450 Cinst. Sum</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>34 #</u>		<u>1350'</u>	<u>450 Cinst.</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>17 #</u>		<u>7500'</u>	<u>750 6000'</u>

Casing Data:

Surface 36 joints of 8 5/8 inch 24 # Grade J-55

Yes (Approved) (Rejected)

Inspected by BW Weaver date 1-2-82

Cementing Program

Size of hole 12 1/2 Size of Casing 8 5/8 Sacks cement required ~~10~~

Type of Shoe used Guide Float collar used yes Btm 3 jts welded yes

TD of hole 1350 Set 1364 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 1364 with 200 sacks neat cement around shoe

+ 400 sax Hewco Lite additives

Plug down @ 1:00 (AM) (PM) Date 1-3-82

Cement circulated Yes No. of Sacks 10

Cemented by Hewco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: 3 Centerloggers