Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

. J.	NM-40029	
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED)

	011	1160	,,,,,	. •		
[DEPARTMEN	NT OF	THE	INTERI	OR	
0/55	GEOLG	GICAL	SUF	RVEY		
	NOTICES	AND	REP	ORTS	ON	WELLS

UNIT A	GREE	MENT NAME	

Or not use this form for proposals to drill or to deepen or plug back to a different servoir, Use Form 9–331–C for such proposals.)

8. FARM OR LEASE NAME Alkali Fed Com

JAN 2-1 1932

1. oil well [X]well

9. WELL NO.

-0 - - - -ARTESIA, OTRICE

2. NAME OF OPERATOR MESA PETROLEUM CO.

10. FIELD OR WILDCAT NAME Undesignated ABO

3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

other

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 33, T5S, R25E

400' FSL & 1980' FEL AT SURFACE:

12. COUNTY OR PARISH 13. STATE Chaves New Mexico

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) GR

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES

Spud,

ABANDON*

SUBSEQUENT REPORT OF: csg & cement

OIL & GAS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

Repart results of multiple completion or zone inge on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well with 17 1/2" hole on 1-9-82. Hit FW at 860'-25 b/hour. Drilled to 922' and ran 23 jts 13 3/8", 48#, H40 casing set at 916'. Cemented with 700 sx HLW + 1# Flocele 4% CaCl, 300 sx Thixset + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 5:00 p.m. 1-11-82. Cement did not circulate. Ran temp survey-TOC at 480'. Set eight plugs with a total of 1150 sx Thixset + 4% CaCl to circule cement. WOC 9 hours then blew hole dry and waited one hour - no fluid. Reduced hole to 12 1/4" and drilled ahead on 1-13-82. WOC total of 36 hours.

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, REM , PARTNERS, ROSWELL , FILE Subsurface Safety Valve: Manu. and Type _____

(This space for Federal or State office use)

18. I hereby certify that the foregoing is true and correct

SIGNED

TIREGULATORY COORDINATORATE

ACCEPTED FOR RECORD CONDITIONS OF HAR ROMANE ANY

___ DATE ___

JAN 2 0 1982

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO