

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

OIL & GAS  
SUBMIT INSTRUCTIONS  
(Other instructions  
on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 29610

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Huggins Draw

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

Undesignated Abo

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 31, T5S, R24E

12. COUNTY OR PARISH

Chaves

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

FEB 24 1982

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Sanders Petroleum Corporation

3. ADDRESS OF OPERATOR

11000-D Spain Rd. N.E., Albuquerque, NM 87111

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

990' FNL & 660' FEL. Sec. 31, T5S, R24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4170 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run Casing & Cement

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 104 jts. 4 1/2" 11.6# J55 casing, set 4224'. Cemented with 200 sx. 65/35 Poz 6% gel., 8 lbs. gilsonite, 5 lbs. salt, 1/2 lb. celloflake, 3% CaCl, followed by 175 sx. Self-Stress with 1% FLA, 1/2 lb. celloflake & 2% CaCl. Plug down 6:28 A.M. 1-18-82. Top of float collar 4181'. Top of cement by temperature survey 2720'.

RECEIVED  
JAN 29 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Helen A. Hoyer

TITLE

Office Manager

DATE

1-27-82

(This space for Federal or State office use)

APPROVED BY

ROGER A. CHAPMAN

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 16 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side