

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other \_\_\_\_\_
2. NAME OF OPERATOR  
Stevens Operating Corporation ✓
3. ADDRESS OF OPERATOR  
P. O. Box 2203, Roswell, New Mexico 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL, 660' FWL, Sec. 11-7S-26E  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
 FRACTURE TREAT ☐  
 SHOOT OR ACIDIZE ☐  
 REPAIR WELL ☐  
 PULL OR ALTER CASING ☐  
 MULTIPLE COMPLETE ☐  
 CHANGE ZONES ☐  
 ABANDON\* ☐  
 (other) Surface casing

SUBSEQUENT REPORT OF:

--	--	--	--	--	--	--	--

RECEIVED  
FEB 5 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
NM-19421-A RECEIVED
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
-----
7. UNIT AGREEMENT NAME  
----- FEB 24 1982
8. FARM OR LEASE NAME  
Hanagan Federal ~~WILL~~ O. C. D. ARTESIA, OFFICE
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Wildcat *Donner*
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11-7S-26E
12. COUNTY OR PARISH | 13. STATE  
Chaves | NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3745' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-9-82      Tex-Mex Rig #1 rig up and spud.

1-10-82 Ran 25 joints of 8 5/8" 24.0# surface casing. Set and cement with 600 sacks 65/35 POZ and 200 sacks Class C, 2% CaCl<sub>2</sub>. Circulate 80 sacks. WOC 18 hrs. Pressure up 1000# for 30 minutes logging no pressure decrease.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that ~~the~~ foregoing is true and correct

ACCEPTED FOR RECORD  
SIGNED WILLIAM A. CHAPMAN TITLE Prod. Coordinator DATE 2-4-82

SIGNED ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY FEB 11 1952  
CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

**\*See Instructions on Reverse Side**