

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR

Stevens Operating Corporation/

3. ADDRESS OF OPERATOR

P. O. Box 2203, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNL, 660 FWL, Sec. 11-7S-26E

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Casing, perforations, tubing

5. LEASE

NM-19421-A

RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

MAR 12 1982

8. FARM OR LEASE NAME

Hanagan Federal

O. C. D.  
ARTESIA, OFFICE

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat Granite

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11-7S-26E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3745 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-9-82 Ran 153 joints 5 1/2" 17.6# casing. Set and cement at 6150' with 220 sacks 65/35 POZ and 350 sacks Self Stress, 2% CaCl<sub>2</sub>. WOC 18 hrs. Pressure up 1000# for 30 minutes logging no pressure decrease.

2-24-82 Perforate at 5999.5, 6000, 6000.5, 6001.5, 6002, 6002.5, 6006.5, 6007.

2-25-82 Ran 194 joints 2 3/8" tubing. Set 5 1/2" Baker Loc-Set packer at 5941', 49' above perfs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Prod. Coordinator DATE 2-25-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

MAR 11 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

RECEIVED  
FEB 26 1982  
OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO