STATE OF NEW MEXICO					300	05-61270	
JEP-17 7-0 MEDEBALS DEPARTME	INT OIL	CONSERVAT	ION DIVISIORE	CEIVED	Form C-101		
DISTRICTION		P. O. HOX 2	2088		Revised 10		
, A1, (A / I,	SA	NTA FE, NEW M	IEXICO 8750 FEB	4 1982	SA. Indicate	Type of Loose	
1/	4			-		5 Gus Louco No.	
CANDOFFICE 1				C. D.	LG-587	**********	
APPLICATION FC		DRILL, DEEPEN,	يتيبين وبدوار بالارام الانان فالمتحد بتعاد متواصيته	A OFFICE			
TTELLOWING	AMENDED 7				7. Unit Aque	LININA AND	
DRILL X		DELPEN	FLUG	васк			
The of Well			SINGLE NU		8. ione or I. Grynbe	erg "LZ" State	
where a symposic sector	OT HER		ICALL	2 ON C []	9. Well No.		
Yates Petroleum Corpo	ration /				3		
207 S. 4th, Artesia, New Mexico 88210						10. Field and Poor, or Wildcat	
and the second	New Mexico		South		Pico	e clare	
UNIT LETTER	n //	ATEC 000	FLET FROM THE POLICE	<u>к. </u>			
660	West	36	55				
					<pre>Fif. conday }</pre>		
					Chaves		
		CHHHH		Nho. Fearing Aho		Determ	
	ANDANANANA 1997 - Peter And	a Cottar Flag, frond (approx. 4250	Abo		Rotary	
3916.3 GL	Blan		L&M Drilling		ASAP		
· · · · · · · · · · · · · · · · · · ·							
	ł,	ROPOSED CASING AN	D CEMENT PROGRAM				
ALLE OF HOLE SIZ		ROPOSED CASING AN		SACKS OF	CEMENT	EST. TOP	
12 1/4	'E OF CASING 8 5/8"			800	sx.	EST. TOP circulated	
12 1/4	E OF CASING	WEIGHT PER FOO	approx. 950'	- +	sx.		
12 1/4	'E OF CASING 8 5/8"	WEICHT PER FOO 24# J-55	approx. 950'	800	sx.		
12 1/4	1E OF CASING 8 5/8" 2" or 52"	WEICHT PER FOO 24# J-55 10.5# - 15.5	T SETTING OLPTH approx. 950' # TD	800 350	SX. SX.	circulated	
12 1/47 7/8" or 6½"4We propose to dri1surface casing wil	LE OF CASING 8 5/8" 12" or 52" 1 and test t 1 be set and	WEICHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul	approx. 950' # TD ermediate format ated to shut off	800 350 ions. A gravel	sx. sx. pproximat and cavit	circulated cely 950' of ng. If needed	
12 1/47 7/8" or 6½"4We propose to drilsurface casing wil(lost circulation)	1 and test t 1 be set and 7 5/8"	WEICHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin	approx. 950' # TD ermediate format ated to shut off g will be run to	800 350 ions. A gravel 1500' a	sx. sx. pproximat and cavir nd cement	circulated cely 950' of ng. If needed ced with	
12 1/47 7/8" or 6½"4We propose to dri1surface casing wil	1 and test t be set and 7 5/8" integraded	WEICHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th	approx. 950 # TD ermediate format ated to shut off g will be run to he surface casing	800 350 ions. A gravel 1500' a g. Tempe	sx. sx. pproximat and cavir nd cement rature su	circulated cely 950' of ng. If needed ced with	
12 1/47 7/8" or 6½"4446889910<	1 and test t be set and 5/8" be set and 7 5/8" inte culated to ti cement top.	WEICHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial,	approx. 950 # TD # TD ermediate format ated to shut off g will be run to be surface casing production casi	800 350 ions. A gravel 1500' a g. Tempe Ing will	sx. sx. pproximat and cavir nd cement rature su be run ar	circulated cely 950' of ng. If needed ced with	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove	1 and test t be set and 7 5/8" inte ulated to ti ement top. er, perforate	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	T SETTING OLDER approx. 950' # TD ermediate format ated to shut off g will be run to be surface casing production casi te as needed for	800 350 ions. A gravel 1500' a g. Tempe ng will producti	sx. sx. and cavir nd cement rature su be run ar on.	circulated cely 950' of ng. If needed ced with	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove	1 and test t be set and 7 5/8" inte ulated to ti ement top. er, perforate	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	approx. 950 # TD # TD ermediate format ated to shut off g will be run to be surface casing production casi	800 350 ions. A gravel 1500' a g. Tempe ng will producti	sx. sx. and cavir nd cement rature su be run ar on.	circulated cely 950' of ng. If needed ced with	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil Surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: FW g	1 and test t be set and 7 5/8" inte ulated to ti ement top. er, perforate gel and LCM t	weicht PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	T SETTING OLDER approx. 950' # TD ermediate format ated to shut off g will be run to be surface casing production casi te as needed for	800 350 ions. A gravel 1500' a g. Tempe ing will producti & KCL wa	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI	circulated cely 950' of ng. If needed ced with	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: FW g BOP PROGRAM: BOP '	1 and test t 1 and test t 1 be set and 7 5/8" inter culated to ti cement top. er, perforate gel and LCM t s will be in	weicht PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	r SETTING OLPTH approx. 950' # TD ermediate format ated to shut off ag will be run to be surface casing production casi is as needed for to 3200', Brine e offset and test	800 350 ions. A gravel 1500' a g. Tempe ing will producti & KCL wa ted daily	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI	circulated cely 950' of ng. If needed ced with	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil Surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: FW g	1 and test t 1 and test t 1 be set and 7 5/8" inter culated to ti cement top. er, perforate gel and LCM t s will be in	weicht PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	APPRO	800 350 ions. A gravel 1500' a c. Tempe Ing will producti & KCL wa ted daily	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR /80	circulated cely 950' of ng. If needed ced with urvey will be nd cemented D. A. M.	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: BOP PROGRAM: BOP PROGRAM: BOP PROGRAM:	1 and test t 1 and test t 1 be set and 7 5/8" inter culated to ti cement top. er, perforate gel and LCM t 's will be in	weicht PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat	APPRO PERN.	800 350 ions. A gravel 1500' a g. Tempe ing will producti & KCL wa ted daily	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR	circulated cely 950' of ng. If needed ted with urvey will be nd cemented D. J.	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: BOP PROGRAM: BOP PROGRAM: BOP COMPANT OTE: Location ha	1 and test t 3 5/8" 3 5/8" 3 or 5½" 1 be set and 7 5/8" inter culated to ti cement top. er, perforater gel and LCM to s will be inter as been moved	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat o 950', Brine stalled at the west by 1320'	APPRO APPRO	800 350 ions. A gravel 1500' a to 1500' a to	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR FOR NG UMDER	circulated cely 950' of ng. If needed ted with urvey will be nd cemented Urwand 32 Urwand 32 DAYS	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: BOP PROGRAM: BOP PROGRAM: BOP PROGRAM:	1 and test t 3 5/8" 3 5/8" 3 or 5½" 1 be set and 7 5/8" inter culated to ti cement top. er, perforater gel and LCM to s will be inter as been moved	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat o 950', Brine stalled at the west by 1320'	APPRO APPRO	800 350 ions. A gravel 1500' a to 1500' a to	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR FOR NG UMDER	circulated cely 950' of ng. If needed ted with urvey will be nd cemented Urwand 32 Urwand 32 DAYS	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove MUD PROGRAM: BOP PROGRAM: BOP PROGRAM: BOP COMPANT OTE: Location ha	I and test t and test t be set and 7 5/8" inte ulated to ti ement top. er, perforate gel and LCM t s will be in as been moved	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat o 950', Brine stalled at the west by 1320'	APPRO A offset and test a offset and test a offset and test APPRO A	800 350 ions. A gravel 1500' a to 1500' a to	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR FOR NG UMDER	circulated cely 950' of ng. If needed ted with urvey will be nd cemented Urwand 32 Urwand 32 DAYS	
12 1/4 7 7/8" or 6½" 4 We propose to dril surface casing wil (lost circulation) enough cement calc run to determine c with adequate cove 10 MUD PROGRAM: FW g BOP PROGRAM: FW g BOP PROGRAM: BOP ' GAS NOT DEDICATED. NOTE: NOTE: Location ha	A DF CASING 8 5/8" 1 and test t 1 be set and 7 5/8" inter- culated to till cement top. er, perforater gel and LCM t s will be in as been moved DECRAMANY ANY. TOTAL ANY.	WEIGHT PER FOO 24# J-55 10.5# - 15.5 he Abo and int cement circul rmediate casin e back into th If commercial, , and stimulat o 950', Brine stalled at the West by 1320'	APPRO A offset and test a offset and test a offset and test APPRO A	800 350 ions. A gravel 1500' a g. Tempe Ing will producti & KCL wa ted daily VAL VALID MT EX.502 ESS 266LL	sx. sx. pproximat and cavir nd cement rature su be run ar on. ter to TI FOR	circulated cely 950' of ng. If needed ced with irvey will be nd cemented Unwhere 32 DAYS 20 DAYS 22 20 20 20 20 20 20 20 20 20	

CILLAND RAN INCOMPANY

TITLE

FEB 8 1982

٠

Which William
ATTHOVAL IF ANY